

ADJUSTABLE STEEL YOKE PIPE ROLL

G


Size Range: 2" (65mm) thru 24" (600mm) pipe

Material: Cast iron roller and steel axle/hanger (Non-metallic polyurethane rollers are available)

Function: For supporting pipe where movement may occur due to thermal expansion.

Manufacturers Standardization Society: ANSI/MSS SP-69 & SP-58, Type 43.

Finish: Plain. Contact customer service for alternative finishes and materials.



Part No.	Pipe Size (in.)(mm)	Rod Size A	B (in.)(mm)	C (in.)(mm)	D (in.)(mm)	E (in.)(mm)	F (in.)(mm)	Maximum O.D. (in.)(mm)	Design load lbs. (kN)	Approx. Wt./100 lbs.(kg)
IC60100050	2" (50)	3/8"-10	1 ⁹ / ₁₆ " (39.7)	4 ³ / ₄ " (120.6)	2 ³ / ₈ " (60.3)	1 ⁷ / ₁₆ " (36.5)	2 7/8" (73.0)	2 5/8" (66.7)	150 (.67)	123 (55.8)
IC60100065	2½" (65)	1/2"-12	1 7/3" (47.6)	6" (152.4)	3 ³ / ₁₆ " (81.0)	2" (50.8)	3 1/4" (82.5)	3" (76.2)	225 (1.00)	178 (80.7)
IC60100080	3" (80)	1/2"-12	2 ³ / ₁₆ " (55.6)	6 5/8" (168.3)	3½" (88.9)	2" (50.8)	3 7/8" (98.4)	3 5/8" (92.1)	310 (1.38)	206 (93.4)
IC60100090	3½" (90)	1/2"-12	2½" (63.5)	7¼" (184.1)	3¾" (95.2)	2" (50.8)	4 3/8" (111.1)	4 1/8" (104.8)	390 (1.73)	267 (121.1)
IC60100100	4" (100)	5/8"-16	2¾" (69.8)	7 7/8" (200.0)	4" (101.6)	2" (50.8)	4 7/8" (123.8)	4 11/16" (119.1)	475 (2.11)	344 (156.0)
IC60100125	5" (125)	5/8"-16	3 ³ / ₈ " (85.7)	9 ³ / ₁₆ " (233.4)	4 ⁹ / ₁₆ " (115.9)	2" (50.8)	5 15/16" (150.8)	5 3/4" (146.0)	685 (3.04)	600 (272.1)
IC60100150	6" (150)	3/4"-20	3 ¹⁵ / ₁₆ " (100.0)	10 3/8" (263.5)	5 ¹ / ₁₆ " (128.6)	2" (50.8)	7" (177.8)	6 3/4" (171.4)	780 (3.47)	800 (362.9)
IC60100200	8" (200)	3/4"-20	5 ¹ / ₁₆ " (128.6)	12 5/8" (320.7)	6 ¹ / ₁₆ " (154.0)	2" (50.8)	9" (228.6)	8 3/4" (222.2)	780 (3.47)	1300 (589.7)
IC60100250	10" (250)	7/8"-22	6¼" (158.7)	14 ¹⁵ / ₁₆ " (379.4)	7 ³ / ₁₆ " (182.6)	2 ¹ / ₁₆ " (52.4)	11 1/8" (282.6)	10 3/4" (273.0)	390 (1.73)	1600 (725.7)
IC60100300	12" (300)	7/8"-22	7 ³ / ₈ " (187.3)	17 ³ / ₈ " (441.3)	8 ³ / ₈ " (212.7)	2¼" (57.1)	13 3/8" (339.7)	13" (330.2)	965 (4.29)	2600 (1179.3)
IC60100350	14" (350)	1"-24	8¼" (209.5)	19" (482.6)	8¾" (222.2)	2¼" (57.1)	14 1/2" (368.3)	14 1/4" (361.9)	1200 (5.34)	3400 (1542.2)
IC60100400	16" (400)	1"-24	9¼" (234.9)	20¾" (527.0)	9¾" (247.6)	2" (50.8)	16 3/8" (415.9)	16 1/8" (409.6)	1200 (5.34)	3900 (1769.0)
IC60100450	18" (450)	1"-24	10 ³ / ₈ " (263.5)	23 ¹¹ / ₁₆ " (601.7)	11 ⁷ / ₁₆ " (290.5)	2 ¹¹ / ₁₆ " (68.3)	18 3/8" (466.7)	18 1/8" (460.4)	1400 (6.23)	4900 (2222.6)
IC60100500	20" (500)	1¼"-30	11½" (292.1)	25 7/8" (657.2)	12¼" (311.1)	2½" (63.5)	20 3/8" (517.5)	20 1/8" (511.2)	1600 (7.11)	6686 (3032.7)
IC60100600	24" (600)	1½"-30	13 ¹³ / ₁₆ " (350.8)	31 ⁹ / ₁₆ " (801.7)	15" (381.0)	3½" (88.9)	24 5/8" (625.5)	24 3/8" (619.1)	1800 (8.00)	11630 (5275.3)