

ROLLER CHAIR

G


Size Range: 2" (50 mm) thru 24" (600 mm) pipe.

Material: Cast iron roller and steel axle/hanger (Non-metallic polyurethane rollers are available)

Function: For supporting pipe where movement may occur due to thermal expansion. Used when ceiling suspension is impractical.

Approvals: Manufacturers Standardization Society ANSI/MSS SP-58 & SP-69, Type 44.

Finish: Plain. Contact customer service for alternative finishes and materials.



Part No.	Pipe Size (in.)(mm)	A (in.)(mm)	B (in.)(mm)	C (in.)(mm)	D (in.)(mm)	E (in.)(mm)	Steel Size (in.)(mm)	Design load lbs. (KN)	Approx. Wt./100 lbs.(kg)
IC60120050	2" (50)	1 1/4" (31.7)	4 5/8" (117.5)	1 1/2" (38.1)	3/8"-16 x 1 1/2"	1 9/16" (39.7)	1/4" x 1 1/4" (6.3 x 31.7)	600 (2.67)	119 (54.0)
IC60120065	2 1/2" (65)	1 1/4" (31.7)	5 3/8" (136.5)	1 5/8" (41.3)	3/8"-16 x 1 1/2"	1 7/8" (47.6)	1/4" x 1 1/4" (6.3 x 31.7)	660 (2.93)	146 (66.2)
IC60120080	3" (80)	2" (50.8)	6" (152.4)	1 3/4" (44.4)	3/8"-16 x 1 1/2"	2 3/16" (55.6)	1/4" x 1 1/4" (6.3 x 31.7)	700 (3.11)	172 (78.0)
IC60120090	3 1/2" (90)	2" (50.8)	6 3/4" (171.4)	2 1/16" (52.4)	3/8"-16 x 1 1/2"	2 1/2" (63.5)	3/8" x 1 1/2" (9.5 x 38.1)	750 (3.33)	264 (119.7)
IC60120100	4" (100)	2" (50.8)	7 1/4" (184.1)	2 5/16" (58.7)	1/2"-13 x 1 1/2"	2 3/4" (69.8)	3/8" x 1 1/2" (9.5 x 38.1)	750 (3.33)	303 (137.4)
IC60120125	5" (125)	3" (76.2)	8 7/16" (214.3)	2 1/2" (63.5)	1/2"-13 x 1 1/2"	3 3/8" (85.7)	3/8" x 1 1/2" (9.5 x 38.1)	750 (3.33)	401 (181.9)
IC60120150	6" (150)	3 1/8" (79.4)	9 3/4" (247.6)	2 3/4" (69.8)	1/2"-13 x 1 1/2"	3 15/16" (100.0)	3/8" x 1 1/2" (9.5 x 38.1)	1070 (4.76)	620 (281.2)
IC60120200	8" (200)	3 3/8" (85.7)	12" (304.8)	3" (76.2)	5/8"-11 x 1 1/2"	5 1/16" (128.6)	3/8" x 1 1/2" (9.5 x 38.1)	1350 (6.00)	874 (396.4)
IC60120250	10" (250)	5 1/4" (133.3)	14 7/16" (366.7)	3 5/8" (92.1)	5/8"-11 x 1 1/2"	6 1/4" (158.7)	1/2" x 2" (12.7 x 50.8)	1730 (7.69)	1270 (576.1)
IC60120300	12" (300)	5 1/2" (139.7)	16 5/8" (422.3)	4 1/8" (104.8)	5/8"-11 x 1 1/2"	7 3/8" (187.3)	1/2" x 2" (12.7 x 50.8)	2400 (10.67)	1918 (870.0)
IC60120350	14" (350)	6" (152.4)	18 1/4" (463.5)	4 5/8" (117.5)	5/8"-11 x 1 1/2"	8 1/4" (209.5)	1/2" x 2" (12.7 x 50.8)	3130 (13.92)	2629 (1192.5)
IC60120400	16" (400)	8" (203.2)	21" (533.4)	5" (127.0)	5/8"-11 x 1 1/2"	9 1/4" (234.9)	5/8" x 2 1/2" (15.9 x 63.5)	3970 (17.66)	3248 (1473.3)
IC60120450	18" (450)	9" (228.6)	23" (584.2)	5 1/4" (133.3)	5/8"-11 x 1 1/2"	10 3/8" (263.5)	5/8" x 2 1/2" (15.9 x 63.5)	4200 (18.68)	4120 (1868.8)
IC60120500	20" (500)	10" (254.0)	25" (635.0)	5 3/4" (146.0)	3/4"-10 x 3"	11 1/2" (292.1)	5/8" x 3" (15.9 x 76.2)	4550 (20.24)	5630 (3553.7)
IC60120600	24" (600)	1 1/2"-30	30" (762.0)	7" (177.8)	3/4"-10 x 3"	13 3/4" (349.2)	3/4" x 3" (19.0 x 76.2)	6160 (27.40)	7702 (3493.6)