

PIPE ROLL WITH SOCKETS

G


Size Range: 2" (25mm) thru 30" (750mm) pipe

Material: Cast iron roller and steel axle/hanger (Non-metallic polyurethane rollers are available)

Function: For supporting pipe where movement may occur due to thermal expansion.

Manufacturers Standardization Society: ANSI/MSS SP-69 & SP-58, Type 41.

Finish: Plain. Contact customer service for alternative finishes and materials.



Part No.	Pipe Size (in.)(mm)	Rod Size A	B (in.)(mm)	C (in.)(mm)	D (in.)(mm)	E Max. O.D. (in.)(mm)	Covering (in.)(mm)	Design load lbs. (KN)	Approx. Wt./100 lbs.(kg)
IC60110050	2" (50)	3/8"-10	2 5/8" (66.7)	4 1/8" (104.8)	1 9/16" (39.7)	3/4" (19.0)	3 3/4" (95.2)	600 (2.67)	119 (54.0)
IC60110065	2½" (65)	1/2"-12	3 1/8" (79.4)	4 7/8" (123.8)	1 7/8" (47.6)	3/4" (19.0)	3 3/4" (95.2)	660 (2.93)	140 (63.5)
IC60110080	3" (80)	1/2"-12	3 3/4" (95.2)	5 1/2" (139.7)	2 3/16" (55.6)	3/4" (19.0)	4 1/2" (114.3)	700 (3.11)	158 (71.6)
IC60110090	3½" (90)	1/2"-12	4 1/4" (107.9)	6 1/8" (155.6)	2 1/2" (63.5)	3/4" (19.0)	5" (127.0)	750 (3.33)	170 (77.1)
IC60110100	4" (100)	5/8"-16	4 3/4" (120.6)	6 3/4" (171.4)	2 3/4" (69.8)	3/4" (19.0)	5 7/8" (149.2)	750 (3.33)	188 (85.3)
IC60110125	5" (125)	5/8"-16	5 13/16" (147.6)	8 1/16" (204.8)	3 3/8" (85.7)	3/4" (19.0)	7" (177.8)	750 (3.33)	246 (111.6)
IC60110150	6" (150)	3/4"-20	6 7/8" (174.6)	9 9/16" (242.9)	3 15/16" (100.0)	1 1/8" (28.6)	8 1/4" (209.5)	1070 (4.76)	504 (228.6)
IC60110200	8" (200)	3/4"-20	8 7/8" (225.4)	11 15/16" (303.2)	5 1/16" (128.6)	1 1/8" (28.6)	10 1/2" (266.7)	1350 (6.00)	658 (298.4)
IC60110250	10" (250)	7/8"-22	11" (279.4)	14 1/16" (357.2)	6 1/4" (158.7)	1 1/8" (28.6)	12 3/4" (323.8)	1730 (7.69)	849 (385.1)
IC60110300	12" (300)	7/8"-22	13" (330.2)	15 13/16" (401.6)	7 3/8" (187.3)	1 1/8" (28.6)	14 3/4" (374.6)	2400 (10.67)	1200 (544.3)
IC60110350	14" (350)	1"-24	14 1/4" (361.9)	17 3/4" (450.8)	8 1/4" (209.5)	1 1/2" (38.1)	16 1/4" (412.7)	3130 (13.92)	2289 (1038.3)
IC60110400	16" (400)	1"-24	16 1/4" (412.7)	19 3/4" (501.6)	9 1/4" (234.9)	1 1/2" (38.1)	18" (457.2)	3970 (17.66)	2497 (1132.6))
IC60110450	18" (450)	1"-24	18 1/4" (463.5))	21 7/8" (555.6)	10 3/8" (263.5)	1 1/2" (38.1)	20 1/4" (514.3)	4200 (18.68)	2899 (1315.0)
IC60110500	20" (500)	1¼"-30	20 1/4" (514.3)	24 1/4" (615.9)	11 1/2" (292.1)	1 1/2" (38.1)	22 1/2" (571.5)	4550 (20.24)	3637 (1649.7)
IC60110600	24" (600)	1½"-30	24 1/4" (615.9)	28 7/8" (733.4)	13 13/16" (350.8)	2" (50.8)	26 1/2" (673.1)	6160 (27.40)	5664 (2569.2)
IC60110750	30" (750)	1½"-30	30 1/4" (768.3)	35 1/2" (901.7)	17 1/4" (438.1)	2" (50.8)	32 1/2" (825.5)	7290 (32.42)	9437 (4280.6)