


HEAVY DUTY SPLIT CLAMP

A







Material: Carbon Steel.
Coating: Zinc Plating ≥ 5 µm (ASTM B 633/EN ISO 2081)
Hot Dip Galvanized (ASTM A153/EN ISO 1461)
Armor X 20
Standards Compliance: Meets MSS SP-58 for pipe supports.

High Load Capacity: Reinforced lock bolts ensure reliable support.
Corrosion Resistance: Different coating options make it suitable for indoor and outdoor & Coastal environments.
Versatility: Suitable for horizontal and vertical applications, compatible with rubber support inserts for chilled water pipes.
Easy Installation: Large opening angle with anti-loss screws for efficient setup.

Part No.	D (mm)	Size (inch)	– DN	Dia (mm)	G	B (mm)	H (mm)	h (mm)	b x s (mm)	Rec. Load KG	Qty Pack
IC12501015	15-19	3/8	10	15	M8/M10	81	55	35	30 x 2.5	200	25
IC12501022	20-25	1/2	15	22	M8/M10	84	58	37	30 x 2.5	200	25
IC12501028	26-30	3/4	20	28	M8/M10	91	64	40	30 x 2.5	200	25
IC12501035	32-36	1	25	35	M8/M10	98	70	43	30 x 2.5	200	25
IC12501042	40-45	1 1/4	32	42	M8/M10	109	80	48	30 x 2.5	200	25
IC12501048	46-51	1 1/2	40	48	M8/M10	115	86	51	30 x 2.5	200	25
IC12501054	53-59	–	–	54	M8/M10	122	93	55	30 x 2.5	200	25
IC12501060	60-64	2	50	60	M8/M10	129	99	57	30 x 2.5	200	25
IC12501070	65-72	–	–	70	M10/M12	136	116	71	30 x 3.0	250	25
IC12501075	74-80	2 1/2	65	75	M10/M12	144	123	74	30 x 3.0	250	25
IC12501083	81-86	–	–	83	M10/M12	152	130	78	30 x 3.0	250	25
IC12501090	87-92	3	80	90	M10/M12	159	136	81	30 x 3.0	250	25
IC12501100	99-109	3 1/2	–	100	M10/M12	175	154	90	30 x 3.0	250	25
IC12501115	109-116	4	100	115	M10/M12	182	160	93	30 x 3.0	250	25
IC12501125	125-133	–	–	125	M10/M12	200	178	102	30 x 3.0	250	25
IC12501140	132-140	–	–	133	M10/M12	207	184	104	30 x 3.0	250	25
IC12501168	159-169	6	150	168	M12,M16	254	220	120	38 x 4.0	380	15
IC12501183	178-188	–	–	183	M12,M16	274	239	130	38 x 4.0	380	15
IC12501203	194-204	–	–	203	M12,M16	290	255	138	38 x 4.0	380	15
IC12501210	203-213	–	–	210	M12,M16	299	264	143	38 x 4.0	380	15
IC12501220	217-227	8	200	220	M12,M16	322	278	150	38 x 4.0	380	2
IC12501250	240-250	–		250	M16	345	302	163	38 x 4.0	380	2
IC12501273	265-275	10	250	273	M16	367	327	175	48 x 5.0	920	2
IC12501315	313-325	12	300	323	M16	414	374	198	48 x 5.0	920	2
IC12501315	354-364	14	350	360	M16	453	412	217	48 x 5.0	920	2
IC12501315	398-410	16	400	406	M16	497	456	239	48 x 5.0	920	2
IC12501315	445-460	18	450	460	M16	548	506	264	48 x 5.0	920	2
IC12501315	499-510	18	500	509	M16	557	557	289	48 x 5.0	920	2

Note: Hot-dip galvanized and stainless steel options are available on request.