



RESTRAINED SIX SPRING MOUNT

E



Enhanced Vibration Isolation: Six spring configurations for high-stability and efficiency in demanding applications.

Restricted Vertical Movement: Limits vertical displacement to ensure equipment stability and controlled movement.

Optimized Diameter Ratio: 0.8 for superior load distribution and stability.

Robust Steel Springs: Engineered to absorb and dampen vibrations effectively.

Leveling Bolt and Cap Screw: Standard in HDG, with stainless steel available on request.

Durable HDG Caps: Heavy-duty upper and lower caps in HDG, with an 8mm rubber base on the lower cap for enhanced friction and isolation.

Applications: Specifically designed for Chillers, Generators, Cooling Towers, and other heavy-duty equipment where controlled movement and stability are essential.

Compliance: Designed to meet BS 1726 (Part 1): 2002 standards

Part No.	Color Code	Rec. Load KG	Max Deflection mm	A	B	L	PCD	D	d	FH	E	F
IC20915900	Orange	900	25	300	270	270	300	16	14	190	80	160
IC209151050	Orange	1050	25	300	270	270	300	16	14	190	80	160
IC209151200	Red	1200	25	300	270	270	300	16	14	190	80	160
IC209151500	Purple	1500	25	300	270	270	300	16	14	190	80	160
IC209151800	Grey	1800	25	300	270	270	300	16	14	190	80	160
IC209152400	Red	2400	25	300	270	270	300	16	14	190	80	160
IC209153000	Brown	3000	25	300	270	270	300	16	14	190	80	160
IC209153600	Black	3600	25	300	270	270	300	16	14	190	80	160
IC209154800	Red	4800	25	300	270	270	300	16	14	190	80	160
IC209156300	White	6300	25	300	270	270	300	16	14	190	80	160
IC209157500	Green	7500	25	300	270	270	300	16	14	190	80	160
IC209157500	Orange	9000	25	300	270	270	300	16	14	190	80	160