


RUBBER CORK SANDWICH MOUNTING PAD

E



Design Feature:

Alternate high/low ribbed construction.
Constructed of a steel plate bonded between Ribbed Anti Vibration Pad.

Optional:

Oil resistance: ASTM D 471-06
Fire rate.
ASTM F 1861.

Applications:

Condensers, AHU, Chiller, Cooling Tower, Generator, Compressor, etc...

Noted:

Dimensions is mentioned with ± 5 tolerance.
To achieve good isolation do not overload.

Part No.	Color Code	Capacity (Kg/cm ²)	Max Deflection mm	A	B	H
IC20922010020	Black	3.75	6	100	100	20
IC20922020020	Black	3.75	6	200	200	20
IC20922030020	Black	3.75	6	300	300	20
IC20922040020	Black	3.75	6	400	400	20
IC20922050020	Black	3.75	6	500	500	20
IC20922060020	Black	3.75	6	600	600	20
IC20922010030	Black	4.6	12	100	100	30
IC20922020030	Black	4.6	12	200	200	30
IC20922030030	Black	4.6	12	300	300	30
IC20922040030	Black	4.6	12	400	400	30
IC20922050030	Black	4.6	12	500	500	30
IC20922060030	Black	4.6	12	600	600	30
IC20922010040	Black	21.23	12	100	100	40
IC20922020040	Black	21.23	12	200	200	40
IC20922030050	Black	21.23	12	300	300	40
IC20922040040	Black	21.23	12	400	400	40
IC20922050040	Black	21.23	12	500	500	40
IC20922060040	Black	21.23	12	600	600	40
IC20922010060	Black	12.2	12	100	100	60
IC20922020060	Black	12.2	12	200	200	60
IC20922030060	Black	12.2	12	300	300	60
IC20922040060	Black	12.2	12	400	400	60
IC20922050060	Black	12.2	12	500	500	60
IC20922060060	Black	12.2	12	600	600	60