

# RUBBER RIBBED MOUNTING PAD (TYPE 1)

E



**Design Feature:**

Alternate high/low ribbed construction.  
Easy to cut pad.

**Optional:**

Oil resistance: ASTM D 471-06  
Fire rate.  
ASTM F 1861.

**Applications:**

Condensers, AHU, Chiller, Cooling Tower, Generator, Compressor, etc...

**Noted:**

Dimensions is mentioned with  $\pm 5$  tolerance.  
To achieve good isolation do not overload.

Part No.	Color Code	Capacity (Kg/cm <sup>2</sup> )	Max Deflection mm	A	B	H
IC20920010010	Black	3.75	3	100	100	10
IC20920020010	Black	3.75	3	200	200	10
IC20920030010	Black	3.75	3	300	300	10
IC20920040010	Black	3.75	3	400	400	10
IC20920050010	Black	3.75	3	500	500	10
IC20920060010	Black	3.75	3	600	600	10
IC20920010015	Black	4.6	6	100	100	15
IC20920020015	Black	4.6	6	200	200	15
IC20920030015	Black	4.6	6	300	300	15
IC20920040015	Black	4.6	6	400	400	15
IC20920050015	Black	4.6	6	500	500	15
IC20920060015	Black	4.6	6	600	600	15
IC20920010020	Black	21.3	6	100	100	20
IC20920020020	Black	21.3	6	200	200	20
IC20920030020	Black	21.3	6	300	300	20
IC20920040020	Black	21.3	6	400	400	20
IC20920050020	Black	21.3	6	500	500	20
IC20920060020	Black	21.3	6	600	600	20