

RUBBER RIBBED MOUNTING PAD (TYPE 2)

E



Design Feature:

Alternate high/low ribbed construction.
Easy to cut pad.

Optional:

Oil resistance: ASTM D 471-06
Fire rate.
ASTM F 1861.

Applications:

Condensers, AHU, Chiller, Cooling Tower, Generator, Compressor, etc...

Noted:

Dimensions is mentioned with ± 5 tolerance.
To achieve good isolation do not overload.

Part No.	Color Code	Capacity (Kg/cm ²)	Max Deflection mm	A	B	H
IC20921010030	Black	12.2	6	100	100	30
IC20921020030	Black	12.2	6	200	200	30
IC20921030030	Black	12.2	6	300	300	30
IC20921040030	Black	12.2	6	400	400	30
IC20921050030	Black	12.2	6	500	500	30
IC20921060030	Black	12.2	6	600	600	30
IC20921010040	Black	12.83	12	100	100	40
IC20921020040	Black	12.83	12	200	200	40
IC20921030040	Black	12.83	12	300	300	40
IC20921040040	Black	12.83	12	400	400	40
IC20921050040	Black	12.83	12	500	500	40
IC20921060040	Black	12.83	12	600	600	40
IC20921010050	Black	15.52	10	100	100	50
IC20921020050	Black	15.52	10	200	200	50
IC20921030050	Black	15.52	10	300	300	50
IC20921040050	Black	15.52	10	400	400	50
IC20921050050	Black	15.52	10	500	500	50
IC20921060050	Black	15.52	10	600	600	50
IC20921010060	Black	20.72	10	100	100	60
IC20921020060	Black	20.72	10	200	200	60
IC20921030060	Black	20.72	10	300	300	60
IC20921040060	Black	20.72	10	400	400	60
IC20921050060	Black	20.72	10	500	500	60
IC20921060060	Black	20.72	10	600	600	60